



# Minipak

## Multiple Residence Telephone Entry

### Specifications:

- ▲ **Design** - Hands-free speaker telephone with internal auto dial capability and remote control of relays.
- ▲ **Directory**- Built-in, 3 x 7 inch, backlit directory.
- ▲ Displays 38 lines of 12 point type, 45 lines of 10 point type. Use 9. point type for 50 lines.
- ▲ **Capacity** - 24, 50, 125\*, 200\*, 300\*, or 400\* residents. Capacity includes 1 to 4 digit directory code, 4 digit direct entry code, and up to 12 digit telephone number for each resident.
- ▲ \*Note: Requires additional Directory
- ▲ **Site ID** - Programmable 4 digit code.
- ▲ **System Security**- Program access code and tamper code.
- ▲ **Dial Mode** - Allows active keypad after dial out.
- ▲ **Call Length** - Unrestricted, or limited from 1 to 4 minutes.
- ▲ **Programming**. Directly on keypad, or remotely via touch-tone telephone.
- ▲ **Power** - 110V/12VAC, 40VA, Class 2, transformer included. .
- ▲ **Output Ratings** - :
  - ▲ Power Relay: 5 AMPS @ 12VDC or 1 AMP @ 110VAC
  - ▲ Alarm Shunt Relay: 250ma @ 12VAC
- ▲ **Output Duration**. Programmable; momentary to 45 seconds, or latched.
- ▲ **Inputs** - Keypad direct entry, or postal lock box/push to-exit button.
- ▲ **Telephone Line** - Standard touch-tone or rotary. Dedicated or extension line.
- ▲ **Mounting** - Surface.
- ▲ **Postal Lock** - Allows keyed access to postman.
- ▲ **Construction** -
  - ⇒ Non-corroding #316 Stainless Steel en-

closure with tamper resistant security screws. .

- ⇒ Double baffled, underwater rated, fiber material speaker.
- ⇒ High quality carbon microphone in an acoustical chamber.



- ▲ **Operating Temperature** - -5° F to + 120° F

### Accessories / Options:

- ▲ **Modem** - Available on all models.
- ▲ **Line Filter** - Suppresses RFI/EMI from input power line.
- ▲ **7-Day Clock** - Allows the creation of automatic unlock schedules.
- ▲ **Printer Option** - Allows connection to serial printer. Logs events as they occur. Requires 7-Day Clock Option.
- ▲ **Card Reader Interface Module** - Supports Weigand 26 protocol reader such as:
- ▲ **RF Remote and Receiver** - allows remote entry
- ▲ **Lighted Hood** - L.E.D. lighting adds additional protection to your unit.
- ▲ **Flush Mount Back Box** - attractive flush mount back box with attractive flushing.

Fiber Optic Compatible International Fiber Systems

### Dimensions / Hookup:



**TRIGON**  
ELECTRONICS, INC.

PH: (951) 371-1730 • FAX (951) 371-2592 • 255 Glider Circle, Corona CA 92880  
www.TrigonElectronics.com.